



## MICA IL6400 LED NiMH

THE IL6400 LED NiMH (RECHARGEABLE) SHARES MANY OF THE GREAT FUNCTIONS WITH THE FULLY PLASTIC IL640.

- The addition of an aluminium clamping ring ensures even better cooling. This is most convenient when you enable the Boost feature by pressing the power button. The boost mode provides nearly 1200 lumens.
- The **IL6400** uses four high-power LEDs with a lifetime of approximately 50,000 hours; This means that you can say goodbye to changing the illuminants. The logo is a guarantee for the highest quality, reliability and easy operation. When the battery is low, the lamp starts flashing at 15-second intervals.

## Technical Data

| <b>Photometric Data</b>            |   |
|------------------------------------|---|
| <b>Illuminant</b>                  | 4 x Cree LED  |
| <b>Luminous flux (REAL Lumen)*</b> | <b>High power:</b> 770 lm<br><b>Low power:</b> 150 lm<br><b>Boost mode</b> 1.170 lm |
| <b>Life time approx.</b>           | 50,000 hrs  |
| <b>General Data</b>                |   |
| <b>Housing</b>                     | Shock-proof polyamide   |
| <b>Lens</b>                        | Hardened glass (5 mm)   |
| <b>Battery</b>                     | NiMH, 6 V   |
| <b>Charging duration</b>           | 11 hrs  |
| <b>Lighting duration</b>           | <b>Highest performance:</b> 8 hrs<br><b>Lowest performance:</b> 24 hrs              |
| <b>Ambient temperature</b>         | - 20 °C to +40 °C   |
| <b>Dimensions (LxWxH) approx.</b>  | 215 x 120 x 125 mm  |
| <b>Weight approx.</b>              | 1,6 kg  |
| <b>IP code</b>                     | IP67  |
| <b>Item no.: (glass panel)</b>     | <b>40_113423</b>  |

**Note:** Charging requires the IL2 (Item no.: 40\_112700) and the power supply ILC (Item no.: 40\_112300).



Application image