



## SETO LANGFELD CONTAINER LUMINAIRE

The **SETO LANGFELD CONTAINERL LUMINAIRE** offers everything you can expect from a container lamp and more.

Modern LED technology ensures powerful and highly efficient illumination of the work area. The milky lens distributes the light homogeneously and enables pleasant, glare-free work.

The construction of high-quality, coordinated plastics makes it extremely robust and resistant. On the other hand, the material mix makes the luminaire extremely light and thus contributes to the low weight of mobile cantainer systems. The shape of the luminaire is flat and at the same time relatively narrow, which means it can also be installed in corners and shafts where typical ceiling lights do not fit.

### PRODUCT FEATURES

- Low power consumption with high luminous efficiency (110 lm / W)
- 120° beam angle
- Compact design
- Light weight



\* The maximum lumen readings given for products with the **REAL Lumen (RL)** quality seal are basically real values in relation of the total product including reflector, diffusor, etc., and not only correspond to the theoretical maximum values of the light source used. For this purpose, we measure appropriately labeled products in our own light laboratory under real conditions of use.

### TECHNICAL DATA

Electrical Data	SW-LB-60	SW-LB-40	SW-LB-20
Operating voltage	110 - 240 V AC		
Power consumption	60 W	40 W	20 W
Photometric Data			
Illumination	LED		
Luminous flux	6.600 lm	4.400 lm	2.200 lm
Luminous flux (REAL LUMEN*)	6.700 lm	4.500 lm	2.300 lm
Life time	> 50.000 h		
CRI	> 80		
Beam angle	120 °		
Colour temperature	5000 K		
General Data			
Dimensions (LxWxH) approx.	1500 x 124 x 43 mm	1200 x 124 x 43 mm	600 x 124 x 43 mm
Item no.:	1424000272	1424000271	1424000270

IP65 2,6  
IP CODE KG

IP65 2,2  
IP CODE KG

IP65 1,05  
IP CODE KG