

ALDEBARAN®  
360 GRAD FLEX LED 600 COMPACT BASIC



## ALDEBARAN® 360 GRAD FLEX LED 600 COMPACT BASIC

- Maximum performance and an unbeatable price / performance ratio were the driving thoughts in the development of the BASIC variant of the successful **ALDEBARAN 360 GRAD FLEX LED 600**. Not only the outstanding light output with 40,000 real lumens\*, but also the optimized weight of only 11 kilograms speak for themselves. The 600 COMPACT BASIC also benefits from almost all the advantages of the products of the proven **360 GRAD FLEX** series.
- This includes shortest set-up and dismantling times, as well as the free directionality of the emitted light through the multi-stage adjustable light modules. The compact design, especially in wind and weather, can fully exploit its advantages over the usual balloons.
- A comprehensive range of useful accessories such as transport boxes, tripods or adapters (e.g. for suspended operation) make the **ALDEBARAN 360 GRAD FLEX LED 600** compact BASIC your budget-friendly universal lighting tool.

### FEATURES

- High lighting power for every budget
- Excellent light power of 40,000 real lumen\*
- Short installation and dismantling times
- Optional accessories



\* The maximum lumen measurements indicated with the quality seal REAL Lumen (RL) on products are generally really achieved values concerning the entire product including reflector, diffusing lens etc. and comply not only with the maximum values of the used illuminant. For this purpose, we measure these marked products on our own laboratory ourselves under real operating conditions.

## TECHNICAL DATA

<b>Electrical Data</b>	
<b>Input voltage</b>	200 -240 V AC
<b>Power consumption</b>	480 W
<b>Photometric Data</b>	
<b>Illuminant</b>	4 x LED module à 120 W
<b>Luminous flux (REAL LUMEN)*</b>	40.000 lm
<b>Colour temperature approx.:</b>	5000 K
<b>CRI</b>	>80
<b>Life time approx.</b>	30.000 hrs
<b>General Data</b>	
<b>Ambient temperature approx.:</b>	-30 °C to +40°C
<b>Dimension approx.:</b>	Ø 235 x 537 mm
<b>Weight approx.:</b>	11 kg
<b>IP code:</b>	IP54
<b>Dimmable:</b>	-
<b>Item no.:</b>	<b>1410001417</b>

\*Lumen = Lm / In the „Lumen REAL“ is REAL measured light output quantities.

## OPTIONAL ACCESSORIES

### PNEUMATIC LIGHT MAST (WITH HAND PUMP MOBILE)

Height max.: 5,75 m / Height min.: 1,81 m / Top load max.: 25 kg

| Item no.: 1410000555 |

### TELESCOPE (WITH AIR FRICTION DAMPING)

Height max.: 4,85 m / Top load max. 25 kg / Weight approx.: 15,4 kg

| Item no.: 1410000329 |

### ELEVATOR TRIPOD

Height max.: 3,70 m / Height min.: 1,67 m / Top load: max. 30 kg / Weight approx.: 21,4 kg

| Item no.: 1410000315 |

### COMPACT TRIPOD

Height max.: 4,58 m / Height min.: 1,12 m / Top load: max. 25 kg / Weight approx.: 13,3 kg

| Item no.: 1410000323 |

### TRANSPORT-BAG

| Item no.: 1410000661 |

### TRANSPORT-BOX

DIMENSION (LXWXH): 725 x 300 x 313 mm

| Item no.: 1410000656 |

### SUSPENSION SET

For suspended use, this set is required.

| Item no.: 1410926011 |