



ALDEBARAN® PROFILINE LED (rechargeable)

- The accumulator version of this luminaire equipped with an additional Li-ion high temperature accumulator which offers at least two hours of illumination in cases where no power grid is available yet or it broke down. In the case of a power outage, it automatically switches to battery operation (emergency light feature).
- In the battery mode, the dimming feature is turned off, and only one LED is shining.
- In the "master" version, the luminaire is configured in a way that additional consumers can be connected and simultaneously switched on and off


Technical Data

Electrical Data	36 W AKKU	36 W MASTER
Input voltage	100-240 V AC	100-240 V AC
Rated current	0,25 A	0,25 A
Power consumption	45 W	45 W
Photometric Data		
Illuminant	4 x 9 W LED Array	4 x (1) 9 W LED Array
Luminous flux approx.	2.800 (2000) lm	2.800 (2000) lm
Colour temperature approx.	4000 K	4000 K
Life time approx.	50.000 hrs	50.000 hrs
General Data		
Battery	2 x Li-Ion, 66 Wh	1 x Li-Ion, 33 Wh
Operating time	> 2 hrs	> 2 hrs
Charging time	4-6 hrs	2-3 hrs
Ambient temperature	-25 °C to +45 °C	-25 °C to +45 °C
Dimension (LxWxH) approx.	700 x 200 x 135 mm	680 x 200 x 135 mm
Weight approx.	5,5 kg	5,3 kg
Protection class	I	I
IP code	IP65	IP65
Specialty	Dimmable 10-100 %, On- / Off switch	Dimmable 10-100 %, On- / Off switch
Item-No.:	14PLLED63WA	14PLLED64WA

▶ Features

- The luminaire runs either via main power supply or the integrated battery. The master version only shines with one LED in the battery mode.
- **Emergency light feature:** In the case of a power outage, the luminaire automatically switches to battery operation. Additional on / off switch.
- Button for dimming feature 10-100% (only in mains operation). In battery mode, the luminaire operates constantly with approx 70 % of the maximum power.
- Integrated charger with status display charges the battery as soon as the light is connected to the mains.
- **Master / slave version:** The master version with emergency light feature switches the slave luminaire along via the integrated socket. Both luminaire are independently dimmable.

Accessories

Item-No.:	Description	Product photo
Item-No.: 1410000206	NYLON STRAPS (for suspension in tents refittable - length 1,2m)	
Item-No.: 1410000654	SOFTBOX (for the transport of max. two ALDEBARAN® PROFILINE Dimensions: 730 x 330 x 200 mm)	