



ALDEBARAN® SMARTLINE RP110 LED



ALDEBARAN® SMARTLINE RP72 LED

## ALDEBARAN® SMARTLINE RP LED SERIES

The luminaires of the **ALDEBARAN® SMARTLINE SERIES** serve as smart replacements for lamps with compact fluorescent technology, convincing with flexibility and efficiency. The simple, timeless design combines a modular basic construction with the advantages of modern and energy-saving LED technology.

In combination with high-quality components such as the anodised aluminium housing, impact-resistant PMMA front screen and cold-resistant end caps, the result is a long-lasting quality product. A variety of options for mounting, suspension and installation maximise the application potential of **SMARTLINE** luminaires.









A low dead weight and the reduced overall height also provide unbeatable advantages on the logistical side.

The luminaires are also available in a dimmable version or with an emergency light function.

### PRODUCT FEATURES

- Wide range of mounting options
- Also available with dimming or emergency light function
- Low weight
- Reduced installation height

## TECHNICAL DATA

Electrical data	SMARTLINE RP110 LED			
	BASIC	BASIC EM	COMFORT	COMFORT EM
Input voltage	100 - 240 V AC	220 - 240 V AC	100 - 240 V AC	220 - 240 V AC
Power consumption	60 W	46 W	60 W	46 W
Lighting data				
Illuminant	LED strip technology			
Luminous	6,500 lm	6,100 lm	5,400 lm	5,100 lm
Luminous (emergency light operation)	–	900 lm	–	500 lm
Colour temperature	4,000 K			
CRI	> 80			
Life time	50,000 h			
General data				
Ambient temperature	-25 to +50 °C	-10 to +40 °C	-25 to +50 °C	-10 to +40 °C
Dimensions (L x W x H)	610 x 160 x 105 mm			
Front pane	PMMA (clear)		PMMA (milky)	
Degree of protection plug / socket (opposite)	Schuko® IP44/54			
Item no.	1417141103	1417241303	1417142103	1417242303
	 	 	 	 

Electrical data	SMARTLINE RP72 LED		
	COMFORT	COMFORT EM	COMFORT DIM
Input voltage	220 - 240 V AC		
Power consumption	34 W	36 W	34 W
Lighting data			
Illuminant	LED strip technology		
Luminous	3,900 lm	3,900 lm	3,900 lm
Luminous (emergency light operation)	–	540 lm	–
Colour temperature	4,000 K		
CRI	> 80		
Life time	50,000 h		
Dimming	No		Yes, stepless from 5 to 100 % (push button)
General data			
Ambient temperature	-25 to +50 °C	-10 to +40 °C	-25 to +50 °C
Dimensions (L x W x H)	485 x 160 x 105 mm		
Front pane	PMMA (milky)		
Degree of protection plug / socket (opposite)	Schuko® IP44/54		Schuko® IP68
Item no.	1417440101	1417443101	1417445201
	