








ALDEBARAN® SMARTLINE RP72 LED COMFORT LOW VOLTAGE

GENERAL DATA

Power consumption: 40 W | **Illuminant:** LED strip technology | **Luminous flux (REAL LUMEN)*** approx.: 3.000 lm | **Colour temperature approx.:** 5000 K | **Ambient temperature:** -25 °C to +40 °C | **IP code:** IP54 | **IP class:** III

MODEL

TYPE	Input voltage	Image	Supply line / Plug connection	Weight	Item no.:
TYPE 12/24V DC	10-35 V DC		Supply line: 5 m supply line H07RN-F 2x1,5mm ² Plug: standard plug 12A for socket (DIN EN ISO 4165) Socket: socket n.a.	1,85 kg	1416952120
	10-35 V DC		Supply line: 5 m supply line H07RN-F 2x1 mm ² Plug: universal connector Socket: socket n.a.	1,85 kg	1416952121
TYPE 24V DC	24 V DC + -15 %		Supply line: 5 m supply line H07RN-F 2x1,5mm ² Plug: CEE 16A/24V DC 10h 2 pole Socket: CEE 16A/24V DC 10h 2 pole (opposite)	2,1 kg	1416952123
TYPE 24V AC	24 V AC +15 % -10 %		Supply line: 5 m supply line H07RN-F 2x1,5mm ² Plug: CEE 16A/24V AC 2 pole Socket: CEE 16A/24V AC 2 pole (opposite)	2,1 kg	1416952130
TYPE 42V AC	42V AC + -15 %		Supply line: 5 m supply line H07RN-F 2x1,5mm ² Plug: CEE 16A/42V AC 12h 2 pole Socket: CEE 16A/42V AC 12h 2 pole (opposite)	2,1 kg	1416952140

Optional accessories: Nylon fixing strap (Set = 2 pcs.)

*Lumen = Lm / In the „REAL Lumen“ is REAL measured light output quantities.

DIMENSIONS

