



with  
**GERM-KILLING**  
effect! [keim-killer.com](http://keim-killer.com)


## GLOBAL SAFE LIGHT

With the **GLOBAL SAFE LIGHT**, SETOLITE has launched a solid and very simple luminaire for **CRISIS SITUATIONS**.

The **GLOBAL SAFE LIGHT** is a 40 W LED light that is equipped with a special lacquer with an antiseptic coating. Thanks to this **antimicrobial lacquer coating**, your surface remains permanently germ-free! For the development of this lamp, we worked closely with the RILIT lacquer factory. The many years of experience and expertise of two well-known and established partners in the market flow together in a product that is unique in this form.

### PRODUCT FEATURES

- Housing made of scratch-resistant aluminium (*anodized*)
- Hardened PMMA lens
- Cold-resistant and unbreakable Ployflor end caps
- Heavy, oil-resistant rubber hose line H07RN-F 3G1.5
- 40 W high-performance LED array  
(corresponds to a 2 x 36 W fluorescent tube)
- Shock and impact resistant

 \* The maximum lumen readings given for products with the **REAL Lumen (RL)** quality seal are basically real values in relation of the total product including reflector, diffusor, etc., and **not only correspond to the theoretical maximum values of the light source used**. For this purpose, we measure appropriately labeled products in our own light laboratory under real conditions of use.

### TECHNICAL DATA

Electrical Data	
Input voltage	230 V AC, 50/60 Hz
Power consumption	40 W
Power factor	0,99
Rated current	0,175 A
Cable	5 m H07RN-F 3G1,5
Photometric Data	
Luminous flux (REAL LUMEN)*	2.800 lm
Colour temperature	5000 K
CRI	> 80
Life time	30.000 h
General Data	
Housing	Aluminium anodized
Front lens	PMMA (milky)
Socket	Schuko IP54
Protection class	I
Dimensions (LxWxH) approx.	485 x 160 x 105 mm
Coating	Antiseptic with brightener and microsilver content
<b>Item no.:</b>	<b>1416210380</b>

**IP54** **1,0**  
IP CODE KG