## **Professional** Lighting Solutions





## **SETO E-POWER MOBILITY PACK**

With the **SETO E-POWER MOBILITY PACK**, there is now also a mobile power source in form of a portable battery from SETOLITE. Fully self-sufficient, the **SETO E-POWER MOBILITY PACK** has up to 2,800 W and 40 Ah, providing enough power for every application. Using the supplied charger, the **SETO E-POWER MOBILITY PACK** is recharged to its full capacity within just 8 hours.

Compact dimensions and a low power-to-weight-ratio make the **SETO E-POWER MOBILITY PACK** the ideal and indispensable companion for mobile use.

## **TECHNICAL DATA**

General data	EP1000	EP2000
Battery type	Li-lon	
Output alternating current	4,1 A	7,3 A
Output AC voltage	230 V AC	
Output power	800 W	1,400 W
Sinus voltage	Pure sinus form	
Output	DC 5 V / 2 A	DC 5 V / 2 A DC 12 V / 3 A
Protective functions	Overload, overcharge, discharge, overtemperature, short circuit, undervoltage	
Charging voltage	29,4 V	54,6 V
Battery capacity	24 V / 40 Ah	48 V / 40 Ah
Charging time	8 h	
Charging cycles	> 3,000	
Ambient temperature	-20 °C to +65 °C	
Dimensions	413 x 260 x 156 mm	408 x 311 x 166 mm
Weight	10 kg	15,5 kg
Item no.:	1428001010	1428001020

IP54



IP54