



SETO FLASHLIGHT FC LED RECHARGEABLE 2.0 (focusable)

The 2.0 version of our multifunctional light power plant with rechargeable battery

In addition to the proven features such as reliability and outstanding light output that already distinguished the predecessor model, the additional functions of the **SETO FLASHLIGHT FC LED RECHARGEABLE 2.0** have also been revised. The tried-and-tested focusing system, which can be operated with one hand offers the right light cone for every application. The two brightness levels (100 and 50 percent) can be selected via the rubberised end cap switch. An additional integrated emergency light function can be switched on or off manually. It is switched on automatically as soon as there is a power failure during a charging process. The protective ring attached to the housing minimises the risk of the light rolling away. Another accessory highlight is the removable and flexibly designed belt clip / holster, which is supplied with the light and allows the **SETO FLASHLIGHT FC LED RECHARGEABLE 2.0** to be worn on the belt.

The **SETO FLASHLIGHT FC LED RECHARGEABLE 2.0** is charged via the charging cradle included in the scope of delivery, which can be operated both via the USB mains adapter and the USB car adapter. The charging cradle can either be placed on a flat surface, e. g. a table-top, or attached to a wall by screwing or sticking it on. The Velcro system supplied means that it does not need to be screwed into the vehicle. The integrated control display shows the current charge status of the luminaire rechargeable battery. The rechargeable battery is a temperature-resistant exchangeable rechargeable battery, which is protected against an undesired memory effect of the rechargeable battery in case of irregular charging cycles by the lithium-ion technology.

PRODUCT FEATURES

- Quickly rechargeable thanks to modern Li-Ion technology
- Convenient one-hand focusing system
- Different light modes (100 and 50 percent, emergency light)
- Velcro system solution for vehicle charging (attachment of charging cradle in vehicle)
- Integrated capacity indicator
- Supplied charging cradle (also available as a multiple CHARGING STATION) can also be used as a wall mount
- Anti-roll ring on the housing
- Belt clip / holster included

TECHNICAL DATA

Electrical data	
Rechargeable battery	1 x 18650 Li-ion rechargeable battery, 3,350 mA, 3.7 V
Operating time	100 % = 12 h 50 % = 22 h
Charging time	approx. 4 h with the supplied USB mains adapter
Light modes	Different light functions (100 % / 50 % / emergency light) Further explanation of emergency light function: see instructions for use
Luminous data	
Illuminant	CREE-XPG 3
Luminous flux (REAL Lumen)*	approx. 450 lm (100 %), approx. 230 lm (50 %)
Colour temperature	6,500 to 7,000 K
CRI	> 70
Life time	50,000 h
General data	
Dimensions (Ø x h)	34 x 163 mm
Weight	142 g (luminaire), 48 g (rechargeable battery)
Item no. (set)	78_0G622C

* Lumen = lm / The "REAL Lumen" are REAL measured light output quantities.
All values are approximate.



SCOPE OF DELIVERY

Luminaire, Li-ion rechargeable battery, charging cradle, USB-C charging cable (1 m), USB mains adapter and USB car adapter, Velcro adhesive pad, detachable and flexibly shaped belt clip / holster.



For products with the quality seal **REAL Lumen** (RL) specified max. Lumen measurements are basically **real** values in relation to the product incl. reflector, diffuser etc. and corresponding **not only to the theoretical** maximum values of the used light source. For this purpose, we measure appropriately labeled products in our own light laboratory under real conditions of use.

OPTIONAL ACCESSORIES

REPLACEMENT RECHARGEABLE BATTERY

Li-ion rechargeable battery + LN 18650 / 3,350 mAh / 3.7 V / 12.39 Wh

Item no.: 78__0G622C-A

CHARGING CRADLE

Charging cradle with USB-C input

Item no.: 78__0G622C-C

BELT CLIP / HOLSTER

To wear on the belt

Item no.: 78__0G622C-H

USB CAR ADAPTER

USB car adapter / input DC 12 – 24 V / output DC 5 V / 2.1 A

Item no.: 78__0G622C-K

USB POWER ADAPTER

USB power adapter (AC/DC) / input 100 – 240 V ~ 50/60 Hz, 0.4 A / output DC 5 V / 2.1 A

Item no.: 78__0G622C-N

USB-C CHARGING CABLE

Cable length: 1 m

Item no.: 78__0G622C-U

VELCRO ADHESIVE PAD

5 x 6 cm, each consisting of 1 x hook and fleece

Item no.: 78__0G622C-V

FIVE-FOLD CHARGING STATION

Charging up to five lights simultaneously

Item no.: 78__0G622C-5X

For optimal use of the luminaire, only the accessories supplied should be used.