



SIGNAL LIGHT EUROLITE II LED

- Enormous lighting duration - 20 hour at full power
- The robust, reliable high-power LED signal light is universally useable with two brightness levels and pivoted lamp head and it is equipped with 3 W LED that make a luminous range of approx. 300 m possible.
- In a power outage, the luminaire switches automatically on (emergency light feature). Charging can be realised either via the 230 V AC plug-in power supply or via the 12 V DC charging adapter.

Technical Data

Photometric Data	
Illuminant	3 W LED
Luminous flux approx.	240 lm
Lighting duration approx.	Level 1: 20 hrs, Level 2: 25 hrs, Level 3: 30 hrs
Luminous range approx.	Level 1: 300 m, Level 2: 210 m, Level 3: 90 m
General Data	
Battery (rechargeable)	6 V 4,5 Ah - maintenance-free
Power supply	9 V 500 mA
Dimensions (LxWxH) approx.	125 x 75 x 300 mm
Weight approx.	1580 g (without charging cradle)
Item-No.:	38_316000

Scope of delivery: EUROLITE II LED, Wall Mount, 230 V charger, 12 V charger adapter, yellow lens, mounting parts, operating manual

▶ Features

- 3 power levels
- Flashing and emergency light feature
- Charging control display
- Pivoted lamp head