



ALDEBARAN® 5000 TUBE

The **ALDEBARAN**® 5000 TUBE light supplies reliable, nearly indestructible LED light. Its place of action is wherever steady illumination of a work space is needed. The extremely robust construction of the Tube has rubber shock protection on both ends and is therefore designed for a long life time and sustainability. By consequently avoiding adhesions, high reparability is guaranteed. Its construction* according to IP 65 makes the use in various environments possible. Also, a linking is possible due to the integrated socket.

PRODUCT FEATURES

- High degree of protection IP65 (water jet protected)
- Preferably for decontamination tents
- Extremely robust construction
- Very easy to clean
- Large rubber end caps protect against impact

*Depending on plug version

TECHNICAL DATA

Electrical Data			
Input voltage	110 - 240 V, 24 W	110 - 240 V, 24 W	110 - 240 V, 24 W
Supply line	5 m H07BQ-F 3G1,5 mm ² with plug CEE white (isolating transformer 16 A - 12 h, 2 P + GND)	5 m H07BQ-F 3G1,5 mm ² with plug IP68	5 m H07RN-F 3G1,5 mm ² with plug IP44
Output	CEE socket white (isolating transformer 16 A - 12 h, 2P GND), IP54	IP68 socket	IP54
Photometric Data			
Illuminant	LED PLL tube 22 W, milky, power supply integrated in 2G11 socket	LED PLL tube 22 W, milky, power supply integrated in 2G11 socket	LED PLL tube 22 W, milky, power supply integrated in 2G11 socket
Luminous flux approx.	1.840 lm	1.840 lm	1.840 lm
Brightness	480 lx in 1 m	480 lx in 1 m	480 lx in 1 m
Colour temperature approx.	4000 - 4500 K, CRI >80	4000 - 4500 K, CRI >80	4000 - 4500 K, CRI >80
General Data			
Tube	Polycarbonate clear, 60 mm, wall thickness 3 mm	Polycarbonate clear, 60 mm, wall thickness 3 mm	Polycarbonate clear, 60 mm, wall thickness 3 mm
Ambient temperature	-30 °C to +40 °C	-30 °C to +40 °C	-30 °C to +40 °C
Dimension (Ø) approx.	120 x 800 mm	120 x 800 mm	120 x 800 mm
Weight (without cable) approx.	1,4 kg	1,4 kg	1,4 kg
Protection class	II	II	II
IP code	IP54	IP65	IP54
*Item-No.:	1450800126	1450800127	1450800129

*The ALDEBARAN® 5000 TUBE LED (1450800126) is also available with 16 W (Ø 120 x 650 mm | 1,3 kg (without cable))

PHOTOMETRIC DATA

