



## ALDEBARAN® FLATLITE 600

- The **ALDEBARAN®** Flatlite is an innovative lighting concept which integrates the latest LED technology (LED strips) in a robust and flat light fixture, predestined for the usage in confined spaces. The Flatlite system is designed for the installation on ceilings or walls, whereby fastening can take place with the help of removable corner pieces, or optionally with customised mountings on the back of the lamp.
- If you are looking for a homogeneous, flicker-free, as well as a space and energy saving lighting for containers, cabins or vehicle bodywork, this Flatlite system is the right option for you. It comes with different designs, which enable operation with a 230 V main circuit or a motor vehicle wiring system.
- Despite low heat generation, all Flatlites are equipped with a polycarbonate front pane for fire safety. The system operates in surrounding temperatures of  $-40^{\circ}\text{C}$  to  $+59^{\circ}\text{C}$  and guarantees easy handling due to rounded corners and edges.

### Optional

- If necessary, Flatlites can be equipped for illumination of work stations with computer screens according to DIN EN 12464-1 and DIN 5035-7. Furthermore, various versions can be fitted with CRI value ( $R_a \geq 90$ ) LEDs in order to illuminate rooms for medical treatments.

## Technical Data

<i>Electrical Data</i>	<b>FLATLITE 600 STANDARD</b>	<b>FLATLITE 600 BN*<sup>1</sup></b>	<b>FLATLITE 600 BAT*<sup>2</sup></b>	<b>FLATLITE 600 BAT BN*<sup>3</sup></b>
<b>Input voltage</b>	<b>230 V</b>	<b>19-32 V DC</b>	<b>230 V</b>	<b>19-32 V DC</b>
<b>Power consumption</b>	32 W	32 W	32 W	32 W
<b>Rated Current (24V)</b>	1.3 A	1.3 A	1.3 A	1.3 A
<i>Photometric Data</i>				
<b>Illuminant</b>	SMD 5050 LED	SMD 5050 LED	SMD 5050 LED	SMD 5050 LED
<b>Luminous flux approx.</b>	2.025 lm	2.025 lm	2.025 lm	2.025 lm
<b>CRI</b>	>80	>80	>80	>80
<b>Colour temperature approx.</b>	4000 K / 5000 K	4000 K / 5000 K	4000 K / 5000 K	4000 K / 5000 K
<b>Life time approx.</b>	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs
<i>General Data</i>				
<b>Ambient temperature</b>	-40 °C to +59 °C	-40 °C to +59 °C	-40 °C to +59 °C	-40 °C to +59 °C
<b>Dimension (LxWxH) approx.</b>	659 x 364 x 25 mm	659 x 364 x 25 mm	659 x 364 x 25 mm	659 x 364 x 25 mm
<b>Weight approx.</b>	5 kg	5 kg	5 kg	5 kg
<b>Item-No.: (fixed supply 4000 K)</b>	<b>14F1603002</b>	<b>14F1603001</b>	<b>14F1603052</b>	<b>14F1603051</b>
<b>Item-No.: (plug / coupling 4000 K)</b>	<b>14F1603007</b>	<b>14F1603006</b>	<b>14F1603057</b>	<b>14F1603056</b>
<b>Item-No.: (fixed supply 5000 K)</b>	<b>14F2603002</b>	<b>14F2603001</b>	<b>14F2603052</b>	<b>14F2603051</b>
<b>Item-No.: (plug / coupling 5000 K)</b>	<b>14F2603007</b>	<b>14F2603006</b>	<b>14F2603057</b>	<b>14F2603056</b>

\*<sup>1</sup> **BN = Vehicle power supply**

\*<sup>2</sup> **BAT = Workstation lighting**

\*<sup>3</sup> **BAT BN = Workstation lighting with vehicle power supply**