



SETO E-POWER MOBILITY PACK
EP4000



SETO E-POWER MOBILITY PACK
EP2000



SETO E-POWER MOBILITY PACK
EP1000

SETO E-POWER MOBILITY PACK

Self-sufficient power source for mobile devices

With the **SETO E-POWER MOBILITY PACK**, there is now also a mobile power source in the form of a portable battery from SETOLITE. The **SETO E-POWER MOBILITY PACKs** can be used completely independently and have different capacities depending on the model, so they always provide enough power for any application.

The **SETO E-POWER MOBILITY PACK** is recharged to its full capacity in just eight hours using the charger included in the scope of delivery. Compact dimensions and a low weight make the **SETO E-POWER MOBILITY PACK** the ideal and indispensable companion for mobile use.

PRODUCT FEATURES

- Self-sufficient use
- Compact dimensions and low weight
- Various protective functions
- Charged within a few hours using the supplied charger
- Lithium-ion rechargeable battery
- Integrated display for charge level indication in per cent
- Impact-resistant trolley case with trolley handle
- AC / DC outputs for various devices

TECHNICAL DATA

| <i>Electrical data</i> | SETO E-POWER MOBILITY PACK | | |
|--------------------------------|---|-------------------------------|----------------------|
| | EP4000 | EP2000 | EP1000 |
| Input voltage | 100 to 240 V AC, 50/60 Hz | | |
| Output alternating current | 10.4 A | 7.3 A | 4.1 A |
| Output AC voltage | 220 to 240 V, 50 Hz | 230 V | |
| Output power | 2,300 W | 1,400 W | 800 W |
| Wave form | Sinusoidal shape | | |
| Output | DC 5 V / 2 A DC 12 V / 3 A | DC 5 V / 2 A DC 12 V / 3 A | DC 5 V / 2 A |
| Protection functions | Overcharge, overload, discharge, overtemperature, short circuit, undervoltage, etc. | | |
| Rechargeable battery | Li-Ion, 48 V / 83 Ah | Li-Ion, 48 V / 40 Ah | Li-Ion, 24 V / 40 Ah |
| Charging voltage | 54.6 V | | 2.4 V |
| Charging time | 7 h | 8 h | |
| Charging cycles | > 3.000 | | |
| <i>General data</i> | | | |
| Dimensions approx. (l x w x h) | 570 x 400 x 260 mm | 408 x 311 x 166 mm | 413 x 260 x 156 mm |
| Ambient temperature | -20 to +65 °C | | |
| Item no. | 1428001040 | 1428001020 | 1428001010 |

